

## Specifications

DK Series Compact Tractors			
Models DK4810   DK5310   DK5810			
ENGINE		BRAKES	
Daedong 4B243DTL-A1		Wet Disk Type	
Liquid Cooled 4 Cylinder Diesel			
2435 cc Displacement		OPERATOR ENVIRONMENT	
48-53-58hp @ 2600 RPM		Front Work Lights with Indicators/Brake Lights	
45 Litre Fuel Tank Capacity		Step Through Platform	
		Under Bonnet Muffler	
TRANSMISSION		Comfort Seat with Seat Belt	
8x8 Synchro Shuttle		Foldable ROPS	
Dry Single Clutch			
Rear Differential Lock		TRAVEL SPEEDS	
4 Wheel Drive		Speed Range 2.17-27.9 km/h	
HYDRAULICS & LINKAGE		DIMENSIONS	
Tandem Gear Hydraulic Pump		Overall Length inc 3PL	3157mm
Manual Linkage Control		Overall Height inc ROPS	2246mm
55.1 l/min Total Flow		Overall Width min tread	1596mm
Category 1 Three Point Linkage		Wheelbase	1810mm
1,232 kg Max Rear Lift Capacity 610mm Behind Lift		Min Ground Clearance	368mm
Power Steering		Weight	1605kgs
POWER TAKE OFF		TYRES	
Hydraulic Independent 540 - 750 rpm PTO		Industrial Tyres R4	Front 10.5 - 16
			Rear 14.9 - 24
*NOTE: The specifications are subject to change for the purpose of improvement without any notice			